

# Fuel Injector Tester & Cleaner Series

## 喷油嘴检测清洗机



**N6A**

内置超声波清洗槽，操作更加方便  
Built-in ultrasonic cleaning bath, easy to operate  
中文、英文、俄文三种语言版本  
Optional languages: Chinese, English, Russian  
数码管显示，简洁耐用  
LED display, make it durable



**G600**

图形化功能界面，操作直观  
Imaging function interface, intuitive operation  
内置超声波清洗槽，操作更加方便  
Built-in ultrasonic cleaning bath, easy to operate  
采用进口西门子油泵，保障使用寿命  
SIEMENS oil pump, ensuring the lifetime



**N2**

专为电喷摩托车设计，提供多种专用接头  
Designed for EFI motorcycles, provides multiple connectors  
超大超声波清洗槽，并带有加热功能  
Ultra big ultrasonic cleaning bath with heating function  
带有全自动检测功能并可自动泄油  
Provides full-automatic testing function with self draining

**功能 | FUNCTIONS**

超声波清洗 Ultrasonic cleaning	加速测试 Accelerating test	中速喷油测试 Medium speed spray value test
怠速测试 (750r/min) Idling test	变速测试 Shifting speed test	高速喷油测试 High speed spray value test
中速测试 (4500r/min) Medium speed test	检漏测试 Leakage test	反向冲洗 Reverse flush
高速测试 (7500r/min) High speed test	怠速喷油测试 Idling spray value test	免拆清洗 Free dismantle cleaning



**L100**

图形化功能界面，操作直观  
Imaging function interface, intuitive operation  
外置超声波清洗槽，检测和清洗和同时进行  
Separated ultrasonic cleaning bath, test and clean at the same time  
采用进口西门子油泵，保障使用寿命  
SIEMENS oil pump, ensuring the lifetime



**N6A+**

外置超声波清洗槽，检测和清洗和同时进行  
Separated ultrasonic cleaning bath, test and clean at the same time  
中文、英文、俄文三种语言版本  
Optional languages: Chinese, English, Russian  
数码管显示，简洁耐用  
LED display, make it durable



**N6C**

抽屉式外置超声波先清洗槽，检测和清洗可同时进行  
Separated draw-out ultrasonic cleaning bath, test and clean at the same time  
中文、英文、俄文三种语言版本  
Optional languages: Chinese, English, Russian  
数码管显示，简洁耐用  
LED display, make it durable

**主要技术参数 | SPECIFICATIONS**

转速范围 Turning speed range	0 ~ 7500r/min	超声波清洗功率 Ultrasonic cleaning power	70W
喷油次数 Pulse numbers	0 ~ 9900 步长 100 0 ~ 9900 times/step length 100	超声波清洗频率 Ultrasonic cleaning frequency	28KHZ±0.5 KHZ
PWM 脉宽 Pulse length	0 ~ 20.0ms 步长 0.1ms 0 ~ 20.0ms step length 0.1ms	量筒容积 Measuring cylinder volume	140ml
系统压力 System pressure	0 ~ 0.6Mpa 可调 0 ~ 0.6Mpa(adjustable)	量筒刻线精度 Groove accuracy of measuring cylinder	0.2ml
油箱容积 Oil box volume	2000 ml	包装尺寸 (主机) Packing size (Main body)	580X540X495mm